Determining Visible Opacity of Emissions Using the Digital Opacity Compliance System II

Look Out EPA Method 9, Here Comes the Digital Equivalent (Finally)

E2S2 Conference Denver

Steve Rasmussen
Hill AFB
Steve.rasmussen@hill.af.mil

Shawn Dolan
Virtual Technology LLC
shawn.dolan@virtuallc.com

www.virtuallc.com

June 16, 2010

	Form Approved
# Report Documentation Page	*Form Approved* *OMB No. 0704-0188*

Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.

1. REPORT DATE **16 JUN 2010**	2. REPORT TYPE	3. DATES COVERED **00-00-2010 to 00-00-2010**

4. TITLE AND SUBTITLE **Determining Visible Opacity of Emissions Using the Digital Opacity Compliance System II. Look Out EPA Method 9, Here Comes the Digital Equivalent (Finally)**	5a. CONTRACT NUMBER
	5b. GRANT NUMBER
	5c. PROGRAM ELEMENT NUMBER
6. AUTHOR(S)	5d. PROJECT NUMBER
	5e. TASK NUMBER
	5f. WORK UNIT NUMBER
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) **75th Air Base Wing,Hill AFB,UT,84056**	8. PERFORMING ORGANIZATION REPORT NUMBER
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)	10. SPONSOR/MONITOR'S ACRONYM(S)
	11. SPONSOR/MONITOR'S REPORT NUMBER(S)

12. DISTRIBUTION/AVAILABILITY STATEMENT
Approved for public release; distribution unlimited

13. SUPPLEMENTARY NOTES
Presented at the NDIA Environment, Energy Security & Sustainability (E2S2) Symposium & Exhibition held 14-17 June 2010 in Denver, CO.

14. ABSTRACT

15. SUBJECT TERMS

16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON
a. REPORT **unclassified**	b. ABSTRACT **unclassified**	c. THIS PAGE **unclassified**	**Same as Report (SAR)**	**28**	

Standard Form 298 (Rev. 8-98)
Prescribed by ANSI Std Z39-18

TECHNICAL APROACH

- DoD Recognition of the <u>Costs</u> and <u>Subjectivity</u> of Method 9 Monitoring Motivated Development of an Alternative Means of Measuring Visible Opacity.

- The DOCS II Technology Rapidly Characterizes Emissions Using:
  - Commercial-Off-The-Shelf Digital Camera
  - Standard Computer
 - DOCS II Emission Characterization Software

Characterization of Visible Emissions to Determine Opacity Compliance 2

DOCS II is Nuisance Characterization

Quantitative verses Qualitative

Emission T1

DOCS II is an easy inexpensive tool for **Quantitative Measurement**

Emission Tn

Opacity ODR %

Is The Emission a Problem? Quantitative

Nuisance Enforcement

Gather Soil Data

Add PM Monitors

Health Effect

Env. Impact

Required Mitigation

What is the Problem Qualitative

Other Projects are tools for Qualitative Measurement

Impact Enforcement

Nuisance Characterization of Visible Emissions for Compliance and Permitting

EPA's Method 9 is used to Quantitatively Assess Visible Emissions

TECHNICAL APROACH

DOCS II Flow

Image Capture → Induction → Analysis → Report → Interface

XML Service Form Print

- Automate Method 9 Opacity Readings
- Provide Compliance Records
- Maintain Credible Evidence

TECHNICAL APROACH

Image Capture

DOCS Flow

Image Capture → Induction → Analysis → Report → Interface

JPG EXIF Example

=

[Nikon3.Quality	] = NORMAL
[Nikon3.WhiteBalance	] = AUTO
[Nikon3.Sharpening	] = AUTO
[Nikon3.Focus	] = AF-S
[Nikon3.FlashSetting	] = NORMAL
[Nikon3.x000A	] = 2/231463
[Nikon3.ISOSelection	] = AUTO
[Nikon3.ThumbOffset	] = 842
[Nikon3.x001A	] =
[Nikon3.ImageAdjustment	] = AUTO
[Nikon3.AuxiliaryLens	] = OFF
[Nikon3.FocusDistance	] = 714/365061
[Nikon3.DigitalZoom	] = 1/722
[Nikon3.AFFocusPos	] = x00010000
[Nikon3.SceneMode	] =
[Nikon3.Saturation	] = 0
[Nikon3.NoiseReduction	] = OFF
[Nikon3.ColorBalance2	] = x0000020C
[Nikon3.x009B	] = 0, 0
[Nikon3.x009C	] =
[Nikon3.x009D	] = 0
[Nikon3.x009E	] = 0, 356, 0, 5, 2, 13, 0, 364, 0, 6
[Nikon3.x009F	] = 2

- **Camera**
    - Min Specifications 2 Mega Pixel ("off the shelf")
    - Refresh Rate Less Than 5 sec.
    - All Brand Specific Features (off)
- **Image, JPG Standard (ISO/IEC IS 10918-1)**
    - Images from Cameras (EXIF)
    - Meta-Data Attributes Identify Camera Settings
    - Pixel Values Set, JPG Compressed
- **Center Plume in Frame with Background**

Images From a Safe Distance Capture The Plume and Background

TECHNICAL APROACH
Induction

DOCS Flow

Image Capture → Induction → Analysis → Report → Interface

- Method 9, 24 Image Minimum
- Dust Opacity, 2 Image Min.
- Opacity Dissipation Rate, 4 Image Min.

- Registration Method
  - Minimization of Variance
    - Same Camera Angle
    - Same Basic Image
    - Difference is Emission
- EXIF Meta Data Cross Check
    - Same Camera
    - Same Settings
   - Checks "Rule" Tolerances

Minimization of Variance Method
(registration algorithm +/- .5 pixel)

Background Effects Neutralized and Emission Isolated

TECHNICAL APROACH

Analysis Theory

Opacity Causes:
- Loss of color
- Loss of detail

Must Quantify both for a valid automated opacity determination

DOCS Flow

Image Capture → Induction → Analysis → Report → Interface

Heavy Dust
Little detail
Little color

Dissipating Dust
More detail
More color

Time

7

TECHNICAL APROACH

Testing and Validating DOCS

Analysis Controlled

Compared to Certified Opacity Readers
Varying Light and Wind
Precision Variance Within Method:
Multiple DOCS Readings
Multiple Certified Reader Readings
Same Source at Same Time

DOCS Flow

Image Capture → Induction → Analysis → Report → Interface

Analysis Controlled

Using Transmisometer Metered Emissions
Smoke School gave Insight Into Accuracy(+/-5%)

Review individual results by selecting icon below.

Opacity: 48

Analysis Field

Compared to Certified Opacity Readers
Precision Variance Within Method:
Multiple DOCS Readings
Multiple Certified Reader Readings
Same Source at Same Time

TECHNICAL APROACH
Reports

DOCS II Emissions Reports

- DOCS II Output Characterization For Visible Emission Sources:
  - Opacity of Image Being Reviewed and Site Field Report (Method 9 Format)
  - Average Opacity Over a Series of Images (Method 9)
  - Opacity Change Over a Series of Images
  - Time Change over a Series of Images
  - Opacity Rate of Change Over Series of Images/Time
  - (Future VEU) "Risk of Nuisance Visibility at a Boundary"
    Requires: Wind Direction and Speed, Location Relative to Boundary

Opacity Observation XML with Images & all Reference Data

Certification Report

Monitoring & Screening Tool, Supporting Compliance & Permitting

DOCS II Enhancements for Fugitive Emissions

- **Fugitive Emissions Have Varying Background**
- Address Background Difference
  - Before and After Image Alignment
  - Isolation of Emission Plume
  - Registration of Plume to Background
- **Fugitive Emission Characterization Requirements**
  - Transient Nature
  - Opacity Compliance Regulations
  - Visibility Compliance Regulations
  - Boundary Visibility "Nuisance" Regulation
- **DOCS Comparison to Known Requirements**
  - Transient Nature Addressed
  - Opacity Compliance Requirement Addressed
  - Visibility Compliance Requirement Addressed (ODR)
  - Boundary Visibility Requirement Addressed

Worked with Multiple Agencies to Identify Required Capability

- # Review of Requirements
  - ## Technical Interchange Outcome
    - Change Requirements
      - Like Existing Method
      - Easy to Adopt
      - Adopted in Permits
    - Boundary Requirements Require
      - Persistence Measurement

Wind Direction →

Fog Generator — 40 yards — 40 yards — 40 yards

25 Yards — 25 Yards — 25 Yards

Camera One — Camera Two — Camera Three

Certified Opacity Readers — Certified Opacity Readers — Certified Opacity Readers

Video Camera

Validate DOCS for Regulatory Acceptance

- Generated Plume Not in Line With Targets Resulting in:
  - Inability to Cross Check Method 9 Readings
    - Where Was the M9 Reading Taken?
    - Relative to Where DOCS Reading Taken?
  - Wind Blew Smoke Beyond Targets at 60, 90, ft No Opacity Recorded
  - Inability to Establish limits of Light or Wind

Outdoor Data (Kickoff) Stdv Opacity

■ M9 STDV   ■ DOCS STDV

(Y-axis: Stdv Opacity, 0–6; X-axis: Offset Distance, 30, 60, 90)

Outdoor Data (Kickoff) Average Opacity

■ M9 Avg   ■ DOCS Avg

(Y-axis: Opacity, 0–45; X-axis: Offset Distance, 30, 60, 90)

Validate DOCS II for Regulatory Acceptance

Requested to Find Light and Wind Limits

Requested to Define Persistence of Emission

- Light Limit >200 LUX
- Wind Limit Between 1 and 15 mph
- Higher Light Less Variance
- Accuracy Could not be Determined
  - Even With Targets In Place Readers Eyes Follow Plume

Indoor Data - Average Opacity

Light - STDV

Indoor Data - Opacity STDV

*Validate DOCS II for Regulatory Acceptance*

Defined Light and Wind Limits

Precision Validated

13

DOCS II Fugitive Emissions
Smoke School Hill Test 10 19 06

- DOCS II Compared to M9 Against Transmissomitor
- Accuracy Established
- Method 9 Certification Distance
  - 45 Feet From Source
- Used Camouflage to Simulate Background of Fugitive Environment


Validate DOCS II for Regulatory Acceptance

*DOCS II Accuracy Validated*

- **Compare DOCS II with Method 9 Compliance Conditions**
- **Constant Source**
  - Fog Generator
  - Extreme Distance

Validate DOCS II for Regulatory Acceptance

DOCS II Just as Reliable In Compliance Conditions as Method 9

- DOCS II Compared to Known Transmissomitor
  - 45 and 90 feet
  - Software Distributed to All Participants
- Validation for TCEQ
  - Revise Ft Hood Tile V to Include DOCS II Implementation and Training
    - Implementation through use of Method 9 users first year DOCS school after that.
   - DOCS School currently under development

Region 6 Smoke School

M9 avg · docs avg · Trans

White Smoke · Black Smoke

Region 6 - Smoke School Opacity Stdv

M9 stdv · DOCS stdv

White Smoke · Black Smoke · Readings

*Validated DOCS II Capability Against Method 9 and Transmissometer* 16

DOCS II Fugitive Emissions
Smoke School Region 8 Test 04 17 07

- Compare DOCS II to Method 9 With a Known Opacity Source
  - DOCS II Accuracy Better
  - DOCS II Precision Better
  - Method 9 Individual Readings
    - Much More Error Than DOCS II
    - Averaged With Multiple Readers
      - Very Close to DOCS II

Region 8 Smoke School

Accuracy (Smoke Schools)

Region 8 - Smoke School Stdv Opacity

Validation of DOCS II Capability

Average Accuracy Validated, Instantaneous Capability Established

*DOCS II Passed Smoke School Just Like Method 9 Readers*

DOCS II Fugitive Emissions ODR Test 4 13 07

- Minimized scale of test to define better define req.
- **Identified Requirements**
  - Source Dissipates Too Fast 17 Seconds to Zero adjusted to every 4 seconds
  - Reading Every 15 Seconds for 6 Min. Like M9 Can Not Be Used
  - Event Definition Images Every 4 sec. High Opacity = Start, Below 2 opacity = End
- Opacity Decay Linear Until Very Low Visibility >3%

**Calculated ODR Duration @ Distance:**
- Half Life: 8.5 Seconds and @ 150 ft
- Life: 17 Seconds and @ 300ft

Validating Opacity Dissipation Rate Calculations

DOCS II Fugitive Emissions ODR Test 4 13 07

Source
62%
D=0
T=0

Opacity Half
Distance 150'
Time 8.5 sec
25%

Opacity Zero
Distance 300'
Time 17 sec
0%

Conclusions:
- Linear Dissipation Valid
- Reynolds Numbers (Mixing) Not Needed
- Plan Revisions Required to Reduce Sequence to 5 sec
Start = First Image
End = Fourth Image

DOCS II Fugitive Emissions ODR Test 5 5 07

- Scraper at Hill AFB
  - 4 Images 5 sec Apart (5 in set)
  - ODR Validation
- Linear Dissipation Valid To Below Visible
- Reynolds Numbers (Mixing) Not Needed
- Can Accurately Predict how fast 'Visible Emission" will Persist

Scraper - ODR

Validating Opacity Dissipation Rate Calculations

# DOCS II Fugitive Emissions ODR Test 5 5 07

- **Aggregate Handling Hill AFB**
  - 4 Images 5 sec Apart (5 in set)
  - ODR Validation

- **Linear Dissipation Valid**

- **Validated Capability to Accurately Determine the Persistence of Opacity**

Aggregate - ODR

Expected —— DOCS ——

Validating Opacity Dissipation Rate Calculations

21

- ## Continuous Source Test To CA Rules
  - Comparison to CA Continuous Method For Continuous Sources
  - Event Start at T=0 and End T=60 min.
  - Readings Every 15 sec. for Hour
    - Average of 3 min From High Opacity
      (12 readings) = Opacity
  - Event Start at T=0 and End T=60 min, Images every 15 sec. (241 to set), High Opacity Image Plus Previous 5 and Next 6 (12 readings) to Compare to Human Readings, High Opacity Image Plus Next 6 used for ODR calc.

Crusher - ODR

— Expected   — DOCS

Opacity: 8, 7, 6, 5, 4, 3, 2, 1, 0

Time: T=0, T=1/2, T=1

22

Validating Opacity Dissipation Rate Calculations

- ## Comparison, CA Road Dust Rules

  - ### Event Start T=0 and End T=5 sec.

  - ### Two Opacity Readings 0 and 5 sec

    - #### Average of two, equal opacity of event

  - ### Event Starts at T=0 and End T=15 sec. Images Every 5 sec. (4 to set), first 2 to Compare to Human Readings all 4 Used for ODR calc.

Scraper (Method 9 - DOCS)

Aggregate (Method 9 - DOCS)

Crusher (Method 9 -DOCS)

Comparing High Variable M9 to Low Variable DOCS II Using Two Readings

Human Opacity Average Higher than DOCS II Average

23

DOCS II
Automating Method 9

- # DOCS II Released to Final Testing 5-08
  - ## Images Validated from Header Record EXIF
  - ## Integrated GPS Locations
  - ## Integrated NOAA 'Weather"
  - ## Streamlined User Interface
  - ## Integrated Solar Tables
  - ## Generated "Most Credible Evidence" argument based on Integrated Output from DOCS II

DOCS II Validated to Determine Instantaneous Opacity and ODR

ASTM Standard
D7520-09
Digital Camera Opacity Technique

- Performance Standard requiring same criteria as Method 9

- Software, Camera and Computer Model Certified in DCOT package

- Certification valid for 3.5 years (lifecycle of computer equipment)

- Operators required to know how to take images and document observation

- DCOT providers responsible for training

Lessons Learned--Risk Reduction

- Industry is significantly concerned with vetting technological solutions

- Method 9 had no perceived scale-up issues when moving from the certification platform to field application

- In contrast, tools based on the new ASTM standard require a significant body of data showing:

  – Certification success

  – Field success against in-stack transmissometers for various stack sizes and configurations

CAA 1990 Amendments, Section 113(e)(1):
    Penalty calculation: "the duration of a violation is established by *any credible evidence,* including evidence other than that in the applicable test method"

Summary

- DOCS II aligns with most aspects of Method 9:
  - Smoke school certification
  - Certification records
- DOCS II certified to ASTM 7520-09 method
- DOCS II can be applied as an equivalent to Method 9
- DOCS II can be used as a field data acquisition support tool in conjunction with traditional human observations
- DOCS II sets a new standard for Credible Evidence in the Visible Emissions measurement.

CAA 1990 Amendments, Section 113(e)(1):
Penalty calculation: "the duration of a violation is established by *any credible evidence*, including evidence other than that in the applicable test method"

The Future of Visual Emissions Opacity Measurements & Data Collection

Handheld Real Time Climatic Sensor

- Handheld Data Collection Device for DOCS II Application
  - One Device Collects all Required Data
  - Error-Free Automated Data Collection

- Integrated Weather Meter, GPS, Rangefinder, & Camera
- Measures all Required Report Data including
    - Weather Conditions - Wind Speed, Wind Direction, Temperature, & Humidity
    - GPS Position Location, Sun Position, & Time
    - Distance to Target Missions Source
    - Digital Images of Visual Emissions & Source
- Creates Digital Reports in the Selected Format
- Only Works as an Upgrade with PC based DOCS II

Coming in 2011

888.872.3836, www.virtuallc.com